

DINONYLPHENOL 90%

DINONYLPHENOL 90% distilled is a viscous liquid, having a light amber color. Application areas for Dinonylphenol include:

- Lube Oil Additives
- Phosphite Stabilizers
- Nonionic Sulfactants
- Dispersants
- Adhesives
- Plasticizer for Resins

SPECIFICATIONS

Property	Range	Test Method
Color, Gardner	7 max.	ASTM D-1544
Nonylphenol, %	10 max.	DP-350
Di-nonylphenol, %	90 min.	DP-350
Water, ppm	1000 max.	PAR-170
Appearance	Clear, free of foreign contamination	Visual

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (072221)

LGP-11[®], LUBE-BOOSTER[®], MAYCO[®], PAROIL[®], SUL-PERM[®], SYN-CHEK[®], SYNKAD[®], CHLOREZ[®], CHLOROWAX 40[®], CHLOROWAX 50[®], DOVERNOX[®], DOVERPHOS[®], DOVERPHOS HIPURE[®], and DOVERPHOS S-9228[®] are federally registered trademarks of Dover Chemical Corporation.