

DOVERPHOS 7

Phenyl Diisodecyl Phosphite

Doverphos 7 is phenyl diisodecyl phosphite (PDDP). It is the highest molecular weight and lowest phosphorus content liquid alkyl-aryl phosphite. **Doverphos 7** is an effective liquid phosphite heat stabilizer for polyurethanes, coatings, ABS, and polycarbonates. Typical use levels range from 0.1 to 3.0% for most applications. **Doverphos 7** can be used in rigid and plasticized PVC applications to give brighter, more consistent colors. Use levels in PVC range from 0.25 to 1.00%.

 $(C_{10}H_{21}O)_2POC_6H_5$

Phenyl Diisodecyl Phosphite

TYPICAL PROPERTIES

Property	Typical Result	
Appearance	Clear Liquid	
Molecular Weight	438	
Phosphorus, %	7.1	
Density, lb/gal	7.8	
Viscosity, cps @ 25°C	17	

SPECIFICATIONS*

Parameter	Specification	Test Method
Color, APHA	50 max	ASTM D1209
Acid Number, mgKOH/gm	0.05 max	ASTM D3242
Refractive Index @ 25°C	1.4780-1.4810	ASTM D1218
Specific Gravity @ 25°C	0.938-0.947	ASTM D1298

^{*}Specifications subject to change without notice.

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (032619)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.