

EM 600
Emulsifier

EM 600 is an emulsifier for use in water soluble metalworking fluids. **EM 600** helps improve wetting characteristics, and offers lubricity and detergency for aiding in dispersion of hard water soaps.

EM 600 is designed for use in soluble oils, synthetics, and semi-synthetics. Formulation guidelines are indicated below:

	<u>% Treat</u>
Soluble Oils	3-7
Semi-synthetics	3-7
Synthetics	2-5

TYPICAL PROPERTIES

Property	Result
pH, 1% in Tap Water	4.4
Specific Gravity, 77°F	1.03
Density (lb/gal)	8.6
Viscosity, SUS @ 100°F (210°F)	310 (65)
Viscosity, cSt @ 40°C (100°C)	61 (11)
Acid Value (mgKOH/g)	7
Pour Point, °F (°C)	65 (18)
Color, ASTM	2

EM 600 should be stored in an original container or bulk storage tank. Prolonged exposure to 0°F may result in solidification. Warming drums between 75-90°F should reverse this. Blending temperatures should not exceed 110°F.

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (111912)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.