

EWS LARD OIL
Lubricity Additive

EWS Lard Oil is an additive that provides excellent lubricity in cutting oils. **EWS Lard Oil** also provides excellent wetting characteristics that will improve surface finish.

EWS Lard Oil can be used in the following areas:

	<u>% By Weight</u>
Straight Oils	3-10

TYPICAL PROPERTIES

Property	Result
FFA as Oleic Acid, %	4 max
Color, ASTM	3 max
Saponification Number	195
Viscosity, SUS @ 100°F	195
Flash Point, COC °F	450 min
Specific Gravity, 60°F	0.915

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (013113)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.