

MAYLUBE E-101
Tridecyl Stearate Ester
Non-Ferrous Lubricity Additive

Maylube E-101 is a fatty ester designed especially for the machining and grinding of aluminum alloys. Although the additive is oil soluble, it can be incorporated into soluble oil, semi-synthetic, and synthetic fluid formulations.

Maylube E-101 has also shown excellent performance in aluminum can making, especially in the “cupping” portion of the process.

Maylube E-101 can also be used in the following areas:

	<u>% Weight</u>
Vanishing Oils	0.5-1.0
Wire Drawing	3-5
Finning Operations	3-5
Aluminum Grinding	3-5
Aluminum Machining	5-10

TYPICAL PROPERTIES

Property	Result
Specific Gravity @ 60/60°F	0.86
Density, lb/gal	7.1
Viscosity @ 100°F (210°F), SUS	95 (35)
Viscosity @ 100°F (210°F), cSt	20 (7.6)
Appearance	Clear Yellow Fluid
Flash Point, °F	>350
Pour Point, °F (°C)	40 (4.4)
Neutralization Number, meqKOH/g	2

Prolonged exposure to cool temperatures may result in solidification. If product freezes, heat to 110-120°F to reconstitute.

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (121112)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.