

MAYSPERM 2011
Sulfurized Sperm Oil Substitute
Non-Staining Sulfurized Additive

Maysperm 2011 duplicates the wear and extreme pressure characteristics typically associated with sulfurized natural sperm oil. It also has excellent corrosion protection and heat stability properties.

Maysperm 2011 can be utilized in grease formulations to provide EP characteristics.

TYPICAL PROPERTIES

Property	Result
Appearance	Dark Brown Fluid
Specific gravity @ 60/60°F (15.6°C)	0.99
Density, lb/gal	8.3
Viscosity @ 100°F SUS (210°F)	3500 (300)
Sulfur Content, % wt.	10.5
Active Sulfur, % wt.	0
Neutralization Number (meqKOH/g)	6.5
Flash Point, C.O.C., °F (°C)	425 (218)
Pour Point, °F (°C)	55 (13)

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (120412)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.