

Doverlube SP-44

Light Colored Sulphur-Phosphorus Additive

Doverlube SP-44 is a light colored, low odor sulphur-phosphorus additive that is free of animal fats and oils.

Doverlube SP-44 has shown excellent stability in various naphthenic oils as well as Group I, II, and III paraffinic oils; also in PAOs and esters.

Doverlube SP-44 can be used as an alternative to chlorinated additives, sulphurised fatty additives, and ZDDP.

Recommended Treat Rates in Formulations:	% Weight
Grinding (Surface, Centerless)	2 – 4
General Machining	3 – 5
Gear Oils	0.5 – 2

Typical Properties

Property	Result
Appearance	Clear Light Yellow Fluid
Color, ASTM D-1500	1.0 max.
Sulphur Content, %	4.4
Phosphorus Content, %	4.3
Copper Strip Test, ASTM D-130	1B
Specific Gravity, 77° F, (25° C)	1.01
Viscosity @ 100° F, SUS	17,000
Viscosity @ 210° F, SUS	320
Acid Value, mgKOH/g	<5
Flash Point, COC, °F	226
4-Bal Wear Test (1% in 150SN) 1800 rpm 130° F 1 hr	0.41 mm
4-Ball EP Weld Test (1% in 150SN) Weld Load	126 Kg

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (120413)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.