



MAYSYN S-168

Fully Formulated Synthetic Fluid Heavy Duty Machining

Maysyn S-168 is a high performance, oil rejecting synthetic fluid formulated for the most severe ferrous, as well as nonferrous, applications. **Maysyn S-168** is designed to outperform EP-fortified soluble oils and semi-synthetics in most operations.

Maysyn S-168 contains no chlorinated, sulfurized, or phosphorus containing additives. In fact, the product's chemical composition, which provides its complete tramp oil rejection property, makes **Maysyn S-168** incompatible with such materials.

Maysyn S-168 possesses both low-foaming characteristics, even in dead soft water, and excellent hard water (600 ppm as CaCO₃) stability. This makes it suitable for use across a broad spectrum of applications and water conditions, even Blanchard and/or Double Disc Grinding in all areas of soft water.

Maysyn S-168, due to its excellent sump life, quick tramp oil rejection, and fine settling characteristics, make it an ideal coolant in either single sump machines or especially central system applications. Longevity is a key item with this product. Starting recommendations are shown below:

	<u>Dilution Levels</u>
Blanchard/Double Disc	40:1 – 25:1
Severe Grinding	40:1 – 20:1
Heavy Duty Machining	20:1 – 10:1

TYPICAL PROPERTIES

Property	Result
Appearance	Clear Yellow
Specific gravity @ 60/60°F (15.6°C)	1.08
Density, lb/gal	9.4
pH, Neat (5% Concentration)	8.7 (8.3)
Acid Value	50
Total Alkalinity, meqHCl/g	8.2

This product is to be kept from freezing.

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (insert date)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.

330-343-7711 · 800-321-8805 · Facsimile 330-365-3926 · www.doverchem.com