



PAROIL 353-NR

Chlorinated Olefin

Extreme Pressure Additive

Paroil 353-NR is a chlorinated olefin. It is a nonflammable, non-corrosive, low volatile liquid at room temperature. **Paroil 353-NR** is a corrosion inhibited grade, designed to eliminate or significantly reduce stain and corrosion occurrence of the workpiece in high humidity and elevated temperature conditions. **Paroil 353-NR** is used in a wide variety of applications including flame retardants, plasticizers, and EP metalworking packages.

Paroil 353-NR is typically (but not limited to) applied in straight oil machining, drawing and stamping fluids. The following information represents typical starting point formulation guides:

	<u>% Weight</u>
Straight Oil (Machining)	3-10
Straight Oil (Drawing and Stamping)	5-30

Paroil 353-NR may be stored in an original container or bulk storage tank. Exposure to 0°F for an extended period will cause significant viscosity increases. To reverse this, drums need to be returned to 80-90°F. Blending should not exceed 130°F. Prolonged exposure to temperatures in excess of 100°F may result in darkening of product and release of corrosive by-products.

Paroil 353-NR contains no substances subjected to reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372.

TYPICAL PROPERTIES

Property	Typical Result
Chlorine, %	53
Specific Gravity @ 25°C	1.29
Density (lb/gal)	10.7
Viscosity @ 210°F, SUS	71
Viscosity @ 100°F, SUS	1,650
Flash Point °F, COC	>400
Color, ASTM	0.5

The information contained on this data sheet is believed to be reliable. Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of the information, the results obtained from the use of the product, or that such use will not infringe on any patent. This information is furnished with the express condition that you will conduct your own tests to determine the suitability of the product for your particular use. (071612)

LGP-11®, LUBE-BOOSTER®, MAYCO®, PAROIL®, SUL-PERM®, SYN-CHEK®, SYNKAD®, CHLOREZ®, CHLOROWAX 40®, CHLOROWAX 50®, DOVERNOX®, DOVERPHOS®, DOVERPHOS HIPURE®, and DOVERPHOS S-9228® are federally registered trademarks of Dover Chemical Corporation.